

(19)



Generated Document.

(11) Publication number: **62278770 A**

PATENT ABSTRACTS OF JAPAN

(51) Intl. Cl.: H01M 8/06 C21C 5/38

(21) Application number: **61120218**

(22) Application date: **27.05.86**

(30) Priority:

(43) Date of application **03.12.87**
publication:

(84) Designated contracting
states:

(71) Applicant: NIPPON KOKAN KK <NKK>
(72) Inventor: FUJII SHIRO

(74) Representative:

(54) RECOVERING METHOD OF CO₂ AND H₂ FROM CONVERTER GAS

(57) Abstract:

PURPOSE: To increase utilization by
treating converter gas with a pressure
swing adsorber (PSA), treating again
with a PSA installed in series, and
supplying the obtained H₂ to a fuel
cell to generate electric power and
recovering exhaust heat as steam.

CONSTITUTION: LD converter gas
is modified to H₂, and treated with a
pressure swing adsorber (PSA) 3
through a absorbin tower 1, and
offgas RH2 which contains other

gasses in addition to H₂ is stored in a holder 4. The offgas RH₂ is treated with a PSA 6 installed in series to obtain H₂. The H₂ obtained is supplied to a negative electrode 13 of a fuel cell 15 and reacted with oxygen in a positive electrode 14 to generate electric power. Exhaust gasses from the negative electrode 13 and the positive electrode 14 are supplied to a combustor 18 to completely burn and exhaust heat is recovered in a boiler 19. Therefore, electric power, steam, and fuel gas can be obtained from offgas from purification equipment of converter gas, and utilization is increased.

COPYRIGHT: (C)1987,JP&Japio

